



# Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

PRO-PACK PART A FSU3780

Page 1 of 4

## MATERIAL SAFETY DATA SHEET

Classified as hazardous according to criteria of Worksafe Australia.

Date of issue: March 2009

### COMPANY DETAILS

AUSTRALIAN SPECIALTY INKS PTY LTD  
A.B.N. 71 002 591 620  
17 REAGHS FARM ROAD MINTO NSW  
2566 (02) 9603-3399  
A/H (02) 979-27790 or mobile 0414 616247

### IDENTIFICATION

Product Name: PRO-PACK PART A FSU3780  
U.N. Number:  
Trade Name:  
Other Names:  
Class: C1  
Hazchem Code: Not applicable  
Manufacturers Code: FSU3780  
Poisons Schedule: S6  
Pack Group: Not applicable  
Use: Product is for use as an ink

### PHYSICAL DATA

Appearance:	Colourless mobile varnish. Strong odour.
Density:	0.87 @ 20°C
Boiling Point/Range:	138°C to 169.7°C
Vapour Pressure:	1.0 kPa @ 20°C
Percent Volatiles:	52
Flash Point:	24°C approx (ABEL)
Flammability Limits(%):	LEL:1.0 UEL:7.0
Solubility in water:	Practically insoluble.



# Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

PRO-PACK PART A FSU3780

Page 2 of 4

Ingredients Chemical entity	CAS No.	Proportion
Acrylic resin		>45%
Aromatic hydrocarbon		>34%
Ester		>17%
UV Stabilizer		>1%
Flow additive		>1%

## HEALTH HAZARD INFORMATION

### HEALTH EFFECTS

Swallowed: May cause irritation to mouth, throat and digestive tract. May cause nausea, diarrhea and vomiting. Large dose may cause unconsciousness.

Eye: Liquid or vapour may cause eye irritation.

Skin: Will cause skin irritation. Prolonged or widespread contact may result in absorption of potentially harmful amounts of material.

Inhaled: Harmful by inhalation. Vapour is irritant to mucous membranes and respiratory tract. Vapours can affect the central nervous system and result in headaches and dizziness. High concentrations of vapours, if exposure is prolonged, may cause unconsciousness. Aspiration of varnish into the lungs can cause serious (even fatal) pneumonitis.

Chronic: Repeated or prolonged skin exposures may produce pronounced irritation and dermatitis.

### FIRST AID

Swallowed: Wash out mouth with water. Give water to drink. Do NOT induce vomiting. If any suspicion of aspiration into the lungs (eg during vomiting) obtain medical advice urgently or contact the Poisons Information Centre. . Keep warm and at rest.

Eye: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical advice urgently.

Skin: Immediately flood the skin with large quantities of water for at least 15 minutes, preferably under a shower. Remove contaminated clothing as washing proceeds. Continue washing for at least 10 minutes. Obtain medical attention urgently. Contaminated clothing should be washed or dry-cleaned before re-use.



# Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

PRO-PACK PART A FSU3780

Page 3 of 4

Inhaled: Remove from exposure. Keep warm and at rest. Allow patient to assume most comfortable position. If breathing stops or shows signs of failing give artificial respiration. If heartbeat absent, give external cardiac compression. Obtain medical attention.

Other Information: Eye wash station and safety shower.

Advice to Doctor: Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

## PRECAUTIONS FOR USE

Exposure Limits: TWA 80 ppm

Engineering Controls: Exposure to this material may be controlled in a number of ways. The measures appropriate for a particular worksite depend on how the material is used and on the potential for exposure. Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions. Ventilation must be explosion proof. If engineering controls and work practices are not effective in preventing or controlling exposure, then suitable personal protective equipment, which is known to perform satisfactorily, should be used.

Personal Protection: Avoid contact with skin, eyes and breathing vapor. Observe good personal hygiene. Wear eye protection (face visor or goggles). Wear chemical resistant gloves. Wear protective clothing as necessary to avoid skin contact. Wear respiratory protection if there is a risk of exposure to high vapor concentrations which meet the requirements of AS/NZS 1715 and AS/NZ 1716. Wear supplied air breathing apparatus in confined spaces. Where applicable, the use of barrier creams before exposure. Where applicable refer to the following Standards: AS/NZ 1337 Eye protectors for industrial applications. AS 2161 Industrial safety gloves and mittens. AS 2210 Safety footwear. AS 3765 Clothing for protection against hazardous chemicals.

Flammability: Highly flammable liquid. Avoid heat and sources of ignition. Prevent build-up of flammable vapours. Hoses should be electrically continuous and containers bonded to avoid static charge build-up. Do NOT smoke.

## SAFE HANDLING INFORMATION

Storage and Transport:

Store away from oxidising agents and foodstuffs. Store in cool well ventilated area away from heat and ignition sources. Containers should always be kept closed in storage and properly labelled. Do not store in low or enclosed areas where vapours may become trapped. Store only in original or approved containers. Mild steel, carbon steel and polypropylene are suitable storage materials, as are lined steel and stainless steel where trace iron or slight discolouration are critical. Galvanised iron, aluminium and copper and its alloys are unsuitable. The product is a scheduled Poison (S6) and must therefore be stored, maintained and used in accordance with the relevant State Poisons Act.



# Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax: (02) 9603-7761

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

PRO-PACK PART A FSU3780

Page 4 of 4

## Spills and Disposal:

Keep public away. Extinguish all ignition sources. Increase ventilation. Avoid contact with liquid. Wear full protective clothing and goggles. For major spills, dam and recover. Prevent entry into drainage systems, rivers etc. Collect with absorbent material such as sand, earth or vermiculite. Collect and place into drums with non sparking tools for recovery or disposal. Warn occupants downwind. Advise authorities. Ensure waste disposal conforms with local waste disposal regulations. Normally suitable for incineration by an approved facility.

## Fire/Explosion Hazard:

Flammable liquid. Use water sprays to cool fire exposed surfaces and any adjacent storage vessels. Shut off source of product if safe to do so. Remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along vapour trail may occur. Avoid contact with strong oxidizing agents and strong caustics. Use foam, CO<sub>2</sub> and dry chemical. Wear full protective clothing and self-contained breathing apparatus. Hazardous decomposition or byproducts: oxides of carbon, (CO<sub>2</sub>, CO).

## Other Information:

### Toxicology

Oral LD50 (rat) 4300mg/kg

Ih1 - Rat LC50: 5000ppm/4h

## Labelling Information:

### RISK PHRASES:

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R65: Harmful: May cause lung damage if swallowed.

### SAFETY PHRASES:

S16: Keep away from sources of ignition - No Smoking

S25: Avoid contact with eyes.

S29: Do not empty into drains.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this label or container.

Contact Point: Technical Director (02) 9603-3399

Date: March 2009