



# Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW 2566

Telephone: (02) 9603-3399 Fax (02) 9603-7761

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

EPOXY THINNER SCREENWASH

Product Number: FER180

## SAFETY DATA SHEET

### 1. IDENTIFICATION

#### Product Identifiers

Product Name: EPOXY THINNER SCREENWASH

Product Number: FER180

Recommended Use of the chemical and restrictions on use: Use as a thinning and cleaning solvent

#### Company Details

AUSTRALIAN SPECIALTY INKS PTY LTD

A.B.N. 71 002 591 620

17 REAGHS FARM ROAD MINTO NSW 2566

(02) 9603-3399

A/H (02) 9792-7790 or mobile 0414 616247

Email: [info@austspecialtyinks.com.au](mailto:info@austspecialtyinks.com.au)

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

#### Emergency Telephone Number

Mob: 0414616247

### 2. HAZARDS IDENTIFICATION

Classified as hazardous according to the Globally Harmonised System of Classification and labeling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Non-dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> Edition).


Poisons Schedule 6

Signal Word: Warning



EPOXY THINNER SCREENWASH

Product Number: FER180

GHS Classification	Pictogram	Hazard Statement
Flammable Liquids – Category 4	N/A	H227 Combustible liquid
Acute Toxicity – Oral Category 4 Acute Toxicity – Dermal Cat 4 Acute Toxicity – Inhalation Cat 4 Eye Irritation – Category 2A Skin Irritation – Category 2		H302 Harmful if swallowed H312 Harmful in contact with skin H332 Harmful if inhaled H319 Causes serious eye damage H315 Causes skin irritation

Precautionary statements:

<b>GENERAL</b> P101 P102 P103	If medical advice is needed, have product container or label at hand Keep out of reach of children Read label before use
<b>PREVENTATIVE</b> P210 P261 P262 P264 P270 P271 P273 P280	Keep away from flames and hot surfaces – No Smoking Avoid breathing fume/mist/vapours/spray Do not get in eyes, on skin or on clothing Wash thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Avoid release to the environment Wear protective gloves/eye protection/face protection
<b>RESPONSE</b> P301+P330+331  P302+P352 P304 + P340  P305+P351+P338  P312 P332+P313 P337+P313 P362 P363 P370+P378	If SWALLOWED: Rinse mouth. Do Not induce vomiting.  If ON SKIN: Wash with plenty of soap and water. If INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing If IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Call a POISON CENTER or doctor/physician if you feel unwell If skin irritation occurs: Get medical advice/attention If eye irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse Wash contaminated clothing before use In case of fire: Use Alcohol stable foam, water spray or fog, dry chemical powder or carbon dioxide.
<b>STORAGE</b> P403+P235 P405	Store in a well ventilated place. Keep cool Store locked up



EPOXY THINNER SCREENWASH

Product Number: FER180

<i>DISPOSAL</i>	
P501	Dispose of contents/container in accordance with local regulations

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients Names and Proportions

Chemical entity	CAS Number	Proportion (%)
2-Butoxyethanol	111-76-2	> 99

4. FIRST-AID MEASURES

Description of necessary first aid measures

Inhalation:	Remove victim from exposure if safe to do so. Administer artificial respiration if breathing is stopped. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. Can be absorbed through skin with resultant toxic effects. Seek immediate medical assistance.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.
Ingestion:	If swallowed, DO NOT induce vomiting. Keep at rest. Transport to nearest medical facility for additional treatment.

Symptoms caused by exposure

Inhalation:	Breathing in vapour will produce respiratory irritation. Breathing in high concentrations can produce central nervous system depression which can lead to unconsciousness.
Skin Contact:	Can result in irritation. Will have a degreasing effect on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. Can be absorbed through the skin. Effects can include those described for swallowing.
Eye Contact:	May result in redness, swelling and/or blurred vision.
Ingestion:	May result in nausea, vomiting and central nervous system depression (similar to drunkenness).



EPOXY THINNER SCREENWASH

Product Number: FER180

**Medical attention and special treatment:**

Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing equipment**

Alcohol stable foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet.

**Specific hazards arising from the chemical**

Carbon monoxide and/or carbon dioxide may be evolved.

**Special protective equipment and precautions for fire fighters**

Combustible liquid. Wear liquid-tight chemical protective clothing and self-contained breathing apparatus if risk of exposure to vapour or products of combustion.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

**Environmental precautions**

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

**Methods and materials for containment and cleaning up**

For small spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.



EPOXY THINNER SCREENWASH

Product Number: FER180

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Avoid breathing of or contact with material. Use in well ventilated areas. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Do not empty into drains. Before eating, drinking or smoking, remove contaminated clothing and wash hands.

### Conditions for safe storage, including any incompatibilities

Do not store near strong oxidants, copper and natural rubber.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Exposure control measures

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia –  
2-Butoxyethanol: 96.9 mg/m<sup>3</sup> (20ppm) TWA (8hr) skin, 242 mg/m<sup>3</sup> (50ppm) STEL

### Biological monitoring

No biological limit allocated.

### Engineering controls

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.



EPOXY THINNER SCREENWASH

Product Number: FER180

### Individual protection measures

<b>Eye and face protection:</b>	Wear safety goggles.
<b>Skin protection:</b>	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.
<b>Respiratory Protection:</b>	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65 <sup>o</sup> C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
<b>Thermal hazards:</b>	Not applicable.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Colourless clear liquid
<b>Odour:</b>	Unpleasant
<b>Odour threshold (ppm):</b>	Data not available
<b>Ph:</b>	Data not available
<b>Melting freezing point (°C):</b>	-65
<b>Initial boiling point and boiling range (°C):</b>	166
<b>Flash point (°C):</b>	68 (closed cup)
<b>Evaporation rate (Butyl acetate = 1):</b>	Data not available
<b>Flammability:</b>	Combustible
<b>Upper/lower flammability or explosive limits (%):</b>	1.1 – 10.6



EPOXY THINNER SCREENWASH

Product Number: FER180

<b>Vapour pressure (kPa@ 20°C):</b>	.10
<b>Vapour density (air = 1):</b>	4.8
<b>Density (g/ml @ 15°C):</b>	.90
<b>Solubility:</b>	Miscible with water
<b>Partition coefficient n-octanol/water:</b>	Data not available
<b>Auto-ignition temperature (°C):</b>	230
<b>Decomposition temperature (°C):</b>	Data not available
<b>Kinematic viscosity (mm<sup>2</sup>/s @ 20°C):</b>	Data not available

10. STABILITY AND REACTIVITY

**Reactivity**

Stable under normal conditions of use.

**Chemical stability**

Stable under normal conditions of use.

**Possibility of hazardous reactions**

Stable under normal conditions of use.

**Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**Incompatible materials**

Strong oxidizing agents, copper and natural rubber.

**Hazardous decomposition products**

Burning can produce carbon monoxide and/or carbon dioxide.



11. TOXICOLOGICAL INFORMATION

<b>Acute toxicity:</b>	Expected to be low toxicity - LD50 Oral (rat): 530-3000mg/kg LD50 Dermal (guinea pig):950- 1414mg/kg
<b>Skin corrosion/irritation:</b>	Mild irritant - Dermal LD50 Oral (rat): 100-610mg/kg Dermal LD50 Dermal (guinea pig):1200- 2000mg/kg
<b>Serious eye damage/irritation:</b>	May irritate the eyes.
<b>Respiratory or skin sensitisation:</b>	Not expected to be a sensitizer.
<b>Germ cell mutagenicity:</b>	Not mutagenic.
<b>Carcinogenicity:</b>	Not a carcinogen.
<b>Reproductive toxicity:</b>	Not expected to impair fertility
<b>Specific Target Organ Toxicity (STOT) – single exposure:</b>	Inhalation of vapours can result in headaches, dizziness, and possible nausea. Inhalation of higher concentrations can produce central nervous system depression and unconsciousness.
<b>Specific Target Organ Toxicity (STOT) – repeated exposure:</b>	Available evidence from animal studies indicates that repeated or prolonged exposure could result in effects on the blood system, liver and kidneys.
<b>Aspiration hazard:</b>	Not considered to be an aspiration hazard.





EPOXY THINNER SCREENWASH

Product Number: FER180

## 12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute toxicity

<b>Fish:</b>	Data not available
<b>Aquatic invertebrate:</b>	Data not available
<b>Algae:</b>	Data not available
<b>Microorganisms:</b>	Data not available

Chronic toxicity

<b>Fish:</b>	Data not available
<b>Aquatic invertebrate:</b>	Data not available
<b>Algae:</b>	Data not available
<b>Microorganisms:</b>	Data not available

### Persistence and degradability

Biodegradable.

### Bioaccumulative potential

Negligible potential to bioaccumulate.

### Mobility in soil

Miscible with water.

### Other adverse effects

Data not available.



EPOXY THINNER SCREENWASH

Product Number: FER180

13. DISPOSAL CONSIDERATIONS

Ensure waste disposal conforms to local waste disposal regulations.

14. TRANSPORT INFORMATION

<b>UN number:</b>	Not applicable
<b>Proper shipping name:</b>	Not applicable
<b>Australian Dangerous Goods class:</b>	Not applicable
<b>Australian Dangerous Goods packing group:</b>	Not applicable
<b>Hazchem code:</b>	Not applicable

15. REGULATORY INFORMATION

<b>Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:</b>	6
<b>Australian Inventory of Chemical Substances (AICS):</b>	Listed
<b>Australian Dangerous Goods class:</b>	Not applicable
<b>Dangerous Goods Initial Emergency Response Guide (SAA/SNZ):</b>	Not applicable



# Australian Specialty Inks Pty Ltd

ABN 71 002 591 620

17 Reaghs Farm Rd, Minto NSW2566

Telephone: (02) 9603-3399 Fax (02) 9603-7761

Website: [www.austspecialtyinks.com.au](http://www.austspecialtyinks.com.au)

EPOXY THINNER SCREENWASH

Product Number: FER180

## 16. ANY OTHER RELEVANT INFORMATION

<b>Date of preparation:</b>	26/11/2016
<b>Revision number:</b>	3
<b>Changes in this revision:</b>	Update to GHS SDS standard